

1925L Desktop 3000 Series 19" LCD Touchmonitor



RENTAL

1925L Desktop Touchmonitor Specifications

Model		1925L
Case/Bezel color		Dark gray
Display type		Active matrix TFT LCD
Display size		19.0" diagonal
Useful screen area	Horizontal	14.8" (376mm)
	Vertical	11.9" (301mm)
Monitor dimensions	Width	17.2" (436mm)
	Height (incl. base)	18.0" (457mm)
	Depth (incl. base)	9.49" (241mm)
Optimal resolution		1024 x 768
Supported resolutions		1280 x 768 at 60, 70 or 75 Hz; 1152 x 864 at 75 Hz; 1024 x 768 at 60, 65, 70 or 75 Hz; 832 x 624 at 75 Hz (Mac); 800 x 600 at 56, 60, 75 or 75 Hz; 720 x 400 at 70 Hz; 720 x 350 at 70Hz; 640 x 480 at 60, 66, 72 or 75 Hz
Colors		16.7 million (8 bit)
Brightness	LCD panel	300 cd/m ²
	LCD panel with touchscreen	AccuTouch: 246 cd/m ² IntelliTouch: 276 cd/m ²
Response time		25 msec (typical)
Viewing angle	Horizontal	+/- 85° or 170° total
	Vertical	+/- 85° or 170° total
Contrast ratio		700:1
Input video format		Digital Video Input (DVI-D); analog; S-Video; NTSC/PAL
Input signal connector		DVI-I; RCA; S-Video on monitor DVI-D; HD-15; S-Video; RCA via cables
Input frequency	Horizontal	31-80 kHz
	Vertical	56-75 Hz
Power supply		External, 85-265Vac, 50-60 Hz Monitor input power 12Vdc @ 3.75A
Power dissipation		40W (typical)
Temperature		Operating 0°C to 40°C; Storage -20°C to 60°C
Humidity		Operating 20% to 80%; Storage 5% to 90%
Weight		21.5lb (9.78kg); shipping 30.0lb (13.6kg)
Warranty	Monitor	3 years
	Touch technology	5 years AccuTouch; 10 years IntelliTouch
	Backlight lamp life	Typical 50,000 hours to half brightness
Other features		Two built-in, rear facing 2W speakers in display head; OSD; lockouts for user controls; VESA75/100 M4; removable base; reversible base for wall mounting; stand rotates from -5° to 90°; touchscreen sealed to bezel