


AccuTouch Five-Wire Resistive For Human-Machine Interface

BENEFITS:

- Stable, drift-free operation
- Broad input flexibility
- Contamination resistance
- Accuracy in high-use applications
- Long product life
- Meets NEMA 4/4x/12 and IP 65 standards




Elo's AccuTouch touchscreens, the proven market leader in five-wire resistive technology, are the preferred solution for applications that demand reliability, input flexibility, and contamination resistance. AccuTouch touchscreens, with its patented technology, deliver a touch response that is drift-free and accurate in high-use applications. Compare the five-wire design of AccuTouch, where both X and Y measurements are made on the stable rear glass layer vs. other resistive technology designs where the flexing plastic coversheet is used to measure one axis. AccuTouch touchscreens provide a longer product life backed by a five-year warranty—withstanding more than 35 million touches vs. the one-year warranty typical with four/eight-wire manufacturers. AccuTouch touchscreens can be sealed against contamination and certified to meet NEMA 4/4x/12 and IP 65 standards. AccuTouch touchscreens are the ideal solution for POS, voting machines, industrial automation, medical equipment, retail, office, and pharmacy automation.

APPLICATIONS:

- Point-of-sale (POS) terminals
- Voting machines
- Industrial automation
- Medical equipment
- Office automation
- Retail automation
- Pharmacy automation



2215 serial controller board and COACh IIs controller chip



Z-border pattern for enhanced linearity

AccuTouch Five-Wire Resistive

MECHANICAL	
Input Method	Finger, gloved hand, or stylus activation
Available Sizes	6.4" to 21.3"; visit our Web site for full specifications and other offerings
ELECTRICAL	
Positional Accuracy	Standard deviation error is less than 0.080 (2 mm)
Resolution	Touchpoint density is based on controller resolution of 4096 x 4096
Touch Activation Force	Typically less than 4 ounces (113 grams)
Controller	Board: Serial (RS232) or USB 1.1 Chip: Serial (RS232)
OPTICAL	
Light Transmission	HL products: 80% +/-5% at 550 nm wavelength Enhanced products: 60% +/-5% at 550 nm wavelength
ENVIRONMENTAL	
Temperature	Operating: -10°C to 50°C Storage: -40°C to 71°C
Relative Humidity	Operating: 90% RH at max 35°C Storage: 90% RH at max 35°C for 240 hours, noncondensing
Altitude	Operating: 10,000 ft (3,048 m) Storage/transport: 50,000 ft (15,240 m)
Chemical Resistance	Industrial chemicals: acetone, methylene chloride, methyl ethyl ketone, isopropyl alcohol, hexane, turpentine, mineral spirits, unleaded gasoline, diesel fuel, motor oil, transmission fluid, antifreeze. Food-service chemicals: vinegar, coffee, tea, grease, cooking oil, salt, plus most commercial cleaners including ammonia-based glass cleaner and laundry detergent.
Electrostatic Protection	Per EN 61000-4-2, 1995: Withstands 20 discharges up to 15 kV
Agency Approvals	UL, cUL, TÜV, CE, FCC Class A
Sealability	Can be sealed to meet NEMA 4 and 12 and IP 65 standards
DURABILITY	
Surface Durability	3H per ASTM D3363
Expected Life	Operationally tested to 35 million touches in one location without failure
Warranty	Touchscreen: 5-year limited warranty Controller: 5-year limited warranty



Find out more about Elo's extensive range of touch solutions. Go to www.elotouch.com, or simply call the office nearest you.

ELO TouchSystems is represented in South Africa by Trading IT, Value Added Distributor & ScreenVision, Value Added Reseller.
Trading IT, Tel (021) 551 2992. Fax (021) 551 2964. Email info@tradingit.co.za. Web www.tradingit.co.za
ScreenVision, Tel (011) 247 1300. Fax (011) 474 8214. Email sales@screenvision.co.za. Web www.screenvision.co.za