

# Projected Capacitive For Outdoor and Through-Glass Applications

## BENEFITS:

- Works outdoors—in rain, snow, ice, and dust
- Touch function operates through customer-installed materials, including vandal-resistant glass up to 18 mm thick
- True flat front surface possible with no bezel
- Works with gloves
- Works even if glass is scratched or broken



**Elo's projected capacitive technology** enables touches to be sensed through a protective layer in front of a display, effectively allowing touchmonitors to be installed behind store windows or vandal-resistant glass. The transparent projected capacitive touchscreen, which is installed between the display and a protective outer layer, allows the complete system to have unsurpassed resistance to impacts, scratches, and vandalism commonly found in public-access applications. The sensing technology is also unaffected by moisture, heat, rain, snow and ice, or harsh cleaning fluids, making it ideal for outdoor applications as well. Offered in two versions: DirectTouch, which consists of a 7.8 mm sensor with tempered glass outer layer, and ThruTouch, which is optimized to work through a customer-installed outer layer. The solid-state touchscreen and controller provide increased levels of reliability and longer life expectancy, resulting in a drift-free response and a low-maintenance unit that requires no recalibration.

## APPLICATIONS:

- Outdoor kiosks
- Ticketing machines
- ATMs
- Web phones
- Pay-at-the pump gas machines
- Through-glass, under-counter, and bartop applications

## Projective Capacitive

MECHANICAL	
Input Method	Finger or gloved hand
Sensor Thickness	DirectTouch: 7.8 mm ThruTouch: 5.8 mm (plus customer supplied glass up to 18 mm thick)
ELECTRICAL	
Positional Accuracy	<1.5% of reported position in recommended viewing area
Resolution	4096 x 4096
Touch Activation Force	No minimum touch activation force is required
Controller	Integral with the screen, with RS232 interface
OPTICAL	
Light Transmission	Up to 88% per ASTM D1003-92
ENVIRONMENTAL	
Temperature	Operating: -15°C to 70°C Storage: -40°C to 70°C
Relative Humidity	Operating: 0°C at 90% RH, noncondensing
Chemical Resistance	Glass is unaffected by cleaning solutions
Electrostatic Protection	Laminated glass assembly complies with EN 60950, UL 60950, and UL 544
Agency Approvals	UL, TÜV Bauart, FCC, CE
Sealability	Can be sealed to meet NEMA 4 and 12
DURABILITY	
Abrasion Resistance	Glass front, unaffected by surface scratching
Expected Life	No known wear-out mechanism from touch
Shock/Vibration	In accordance with UL291 when installed in a suitable correct bezel
Impact Resistance	Meets UL-60950 and CSA C22.2 No. 60950 ball drop test (0.5 kg, 50 mm diameter ball dropped from height of 1.3 m)
Water	Resistant to water droplets on the surface
Weather	Resistant to snow, ice, rain, sleet, hail, wind, etc.
Warranty	2-year limited



Find out more about Elo's extensive range of touch solutions. Go to [www.elotouch.com](http://www.elotouch.com), or simply call the office nearest you.

<b>Corporate Headquarters</b>	800-ELO-TOUCH Elo TouchSystems, Inc. 6500 Kaiser Drive Fremont, CA 94555	<b>Europe Headquarters</b>	Tel +32 (0)16 35 21 00 Fax +32 (0)16 35 21 01 eloinfo@elotouch.com	<b>Asia-Pacific Headquarters</b>	Tel +81 (45) 478-2161 Fax +81 (45) 478-2180 www.tps.co.jp	<b>Latin America Headquarters</b>	Tel 1-305-717-6715 Fax 1-305-717-4909 www.elotouch.com.ar
-------------------------------	---	----------------------------	--	----------------------------------	---	-----------------------------------	---

Elo TouchSystems reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Copyright 2004 Elo TouchSystems, Inc. All other trademarks are the property of their respective owners. Printed in Belgium January 04